

OPERABLE, VERTICAL LIFT & ACCORDION PARTITIONS

VINYL COLOR SELECTOR



The vinyl patterns and colors shown in this selector are included in the price of Hufcor Operable, Vertical Lift and Accordion partitions which are manufactured in the United States.





VINYL COLORS

FOR OPERABLE, VERTICAL LIFT & ACCORDION PARTITIONS

BAXTER PATTERN

NOT recommended for use on a tackable surface. Tack holes will become visible over time. Pattern is a random match.



44-534
Stone

44-532
Cream

44-535
Seafoam

44-533
Lemon Grass

44-536
Brown

FUSION PATTERN

NOT recommended for use on a tackable surface. Tack holes will become visible over time.



44-537
White

44-538
Light Grey

44-539
Beige

44-540
Silver & Gold

44-541
Silver Grass

KAMAKURA PATTERN

NOT recommended for use on a tackable surface. Tack holes will become visible over time. Pattern is a random match.



44-542
Ghost Ship

44-543
Sand

44-546
Rowboat

44-544
Beehive

44-545
Everglades

Actual color provided may vary from swatch shown due to dye lot variations. Room lighting may also change the color's appearance.





HIGHLAND PATTERN

Recommended for use on a tackable surface. The embossed surface helps to conceal pin holes. Pattern is a random match.



44-237
Cloud

44-231
White Rice

44-274
Dover

44-236
Beach

44-218
Coffee Cream

HIGHLAND PATTERN

Recommended for use on a tackable surface. The embossed surface helps to conceal pin holes. Pattern is a random match.



44-527
Truffle

44-227
Stone



ASIAN LINEN PATTERN

NOT recommended for use on a tackable surface. Tack holes will become visible over time.



44-501
Alabaster

44-505
Parchment

44-502
Berber

44-503
Grey

44-530
Mushroom

Actual color provided may vary from swatch shown due to dye lot variations. Room lighting may also change the color's appearance.



CAIRN PATTERN

NOT recommended for use on a tackable surface. Tack holes will become visible over time. Pattern is a random match.



44-239
Dover

44-242
Beige

44-241
Wheat

44-507
Camouflage

44-244
Pearl

CAIRN PATTERN

NOT recommended for use on a tackable surface. Tack holes will become visible over time. Pattern is a random match.



44-305
Grey

44-306
Grey Flannel

44-246
Stone

44-521
Denim

44-524
Black

WOODTONE

NOT recommended for use on a tackable surface. Tack holes will become visible over time.



44-531
Wilshire Cherry



Actual color provided may vary from swatch shown due to dye lot variations. Room lighting may also change the color's appearance.



A word about vinyl and the environment.

The wallcoverings industry is carefully monitored by various government agencies, including OSHA and Congress, to ensure that the product's manufacture, installment and use are safe for the environment. Hufcor's wallcoverings are manufactured without heavy metals including lead, mercury, chromium or cadmium that could adversely affect the environment.

The primary raw material in vinyl resin comes from common salt, which is in abundant supply. This means that vinyl is less reliant on petroleum resources than other plastics. The vinyl manufacturing process is highly efficient – more than 99 percent of all vinyl produced ends up in a finished product.

Hufcor's standard vinyl wallcoverings, manufactured by OMNOVA Solutions, are compliant with the performance standards established for low-emitting wallcovering by California Department of Public Health (CDPH) in classroom and office settings, and are compliant with the California Collaborative for High Performance Schools (CHPS) and the LEED for Schools programs. Qualified project uses of this vinyl wallcovering may be eligible for CHPS and LEED credits under their respective Ceiling and Wall Systems Programs.

Wallcoverings are designed to meet applicable regulations and standards and are tested in an outside third party laboratory for flame spread and smoke levels.

Vinyl wallcoverings are more resistant to scratching and tearing than alternate coverings. Typically, vinyl wallcoverings last three to five times longer than other surface treatments.

*Additional standard finishes may be found on our website, www.hufcor.com.

HUF COR STANDARD
VINYL WALLCOVERINGS,
MANUFACTURED BY
OMNOVA SOLUTIONS,
ARE MAS CERTIFIED
GREEN® FOR THEIR
LOW VOC EMISSIONS.





SPECIFICATIONS

FOR OPERABLE, VERTICAL LIFT & ACCORDION PARTITIONS

TYPE II, CLASS A, VINYL SPECIFICATIONS	PATTERNS Highland, Cairn, Asian Linen, Baxter, Kamakura, Fusion, Woodtone Wilshire Cherry
Minimum Weight	20 oz./lin. yd.
Average Width	54" [1372mm]
Mildew Resistant	x
CCFA-W-101	x
CCC-W-408A & C	x
Flame Developed	20 gypsum /10 cement board
Smoke Developed	45 gypsum /20 cement board
MEA Approved N.Y. Dept of Buildings	x
NFPA 101-94 when tested by ASTM E84-91	x

ADDITIONAL PRODUCT FEATURES

- Compliant with the performance standards established for low-emitting wallcovering by LEED v4 and the California Department of Public Health (CDPH) in classroom and office settings. Compliant with the California Collaborative for High Performance Schools (CHPS).
- Contains additives to resist mold and other micro-biological growth on the decorative surface of the product. These additives, however, will not prevent mold growth if moisture is allowed to accumulate in or behind the wall.
- PFOA free – does not contain, nor will it degrade to, Perfluoro Octanoic Acid (PFOA).
- NFPA 101 and IBC Class A interior wall finish rating when tested using ASTM-E84 method of reinforced cement board and Type X gypsum board and when tested in accordance with NFPA 286.



CLEANING INSTRUCTIONS

Common dirt and stains may be removed from wallcovering by rubbing lightly with a moistened cloth, sponge or stiff bristle brush using a mild soap, detergent or non-abrasive cleanser. It is important that clean water be continuously used and that the material be towel dried.

CAUTION: Strong organic solvents (such as ketones) and harsh abrasive cleaners are not recommended. These materials will cause dulling, discoloration or softening of the vinyl, possibly resulting in permanent damage.

*Additional standard finishes may be found on our website, www.hufcor.com.

Hufcor has a program of continuous product improvement and as a result reserves the right to improve and change products, design, and/or specifications without notice.



P.O. Box 5591 • 2101 Kennedy Rd.
Janesville, WI USA 53547-05591
Tel: 608-756-1241 or 800-356-6968
Fax: 608-758-8253 • Email: info@hufcor.com
www.hufcor.com

F-4340A 03/16 HUF



*USGBC and related logo is a trademark owned by the U.S. Green Building Council and is used by permission.



The quality systems of Hufcor's manufacturing facilities are registered to the ISO 9001 standards.